



Home of the EZroll off
SPECIFICATIONS DATA FOR
Model EZ12TR
EZroll off Trailer

<i>Hoist Rated capacity:</i>	12,000 lbs.
<i>Hoist Frame:</i>	6" x 3" x 1/2" wall tube.
<i>Main Frame:</i>	5" x 3" x 3/8" wall tube.
<i>Front Stops:</i>	5/8" plate.
<i>Safety Lock:</i>	Automatic Mechanical.
<i>Hoist Cylinder:</i>	2- 3"x 30"x 2" Chrome Rods.
<i>Winch Cylinder:</i>	2- 4"x 36"x 2" Nitro Rods.
<i>Cable:</i>	5/8" Cable.
<i>Outside Rollers:</i>	3" O.D. w/bronze bearing.
<i>Cable Sheaves:</i>	8" O.D. w/bronze bearing.
<i>Cable Travel:</i>	144"
<i>Hinge Shaft:</i>	1-1/2" with grease zerks.
<i>Dump Angle:</i>	51 degrees.
<i>Trailer Weight, Width, Length:</i>	3500 lbs, 100"W, 211"L
<i>Approximate Operating Times:</i>	- Down 17 sec. - On 38 sec. - Off 32 sec.
<i>Dumpster Style:</i>	Tub
<i>Maximum Dumpster Size:</i>	10 cubic yards.
<i>Hydraulics:</i>	- All hydraulics have safety lock valves. - Electric over hydraulic with manual override. - Wireless remote controlled operation. - 2 5/16" Ball or Pintel. - Hydraulic wireless remote controlled. - Five-year structural. - 13 Hp Honda engine - electric start, backup recoil start, 10/2 gpm pump at 2000 psi. - UHMW slide push bar. - Dual container locks front and back. - Hydraulic front tongue jack. - Aluminum diamond plate motor cover. - Oil bath hubs on axles. - LT 235/R16 (Tires) - Torflex axles 6,000 lbs with electric brakes. - Semi Auto Tarper. - Fully Auto Tarper (wireless remote control) - Detachable or welded on Gooseneck.
<i>Hitch:</i>	
<i>Jack:</i>	
<i>Warranty:</i>	
<i>Other:</i>	
<i>Popular Options:</i>	

Note: Materials and product improvement is a continuous commitment at NEDLAND INDUSTRIES, INC. These specifications are subject to change without notice.

Mailing address:
P.O.Box 217
Ridgeland, Wisconsin 54763

Delivery address:
315 Railroad Street
Ridgeland, Wisconsin 54763