



*Home of the EZrolloff*  
**SPECIFICATIONS DATA FOR  
Ezrolloff Truck Hoist**

<i>Hoist Rated capacity:</i>	20,000 lbs.
<i>Hoist Frame:</i>	3" x 6" x 3/8" wall tube.
<i>Front Stops:</i>	5/8" plate.
<i>Safety Lock:</i>	Automatic Mechanical.
<i>Hoist Cylinder:</i>	2- 4" x 48" x 2" Chrome Rods.
<i>Winch Cylinder:</i>	2- 4" x 48" x 2" Nitro Rods.
<i>Cable:</i>	5/8" Cable.
<i>Outside Rollers:</i>	3" O.D. w/bronze bearing, greaseable.
<i>Cable Sheaves:</i>	8" O.D. w/bronze bearing, greaseable.
<i>Cable Travel:</i>	192"
<i>Hinge Shaft:</i>	1-1/2" solid with grease zerks.
<i>Dump Angle:</i>	51 degrees.
<i>Hoist Length:</i>	- 14'6"
<i>Extendable Tail:</i>	- 24" Hydraulic operated tail.
<i>Hydraulics:</i>	- Electric over hydraulic.(with manual override) - <b>Wireless remote controlled operation.</b> - Tipp hoist cylinders have automatic leveling controls and lock valves. - UHMW Slide Pulley Block.
<i>Dumpsters Style:</i>	- Cable pull.
<i>Maximum Dumpster Size:</i>	- 30 Cubic yard.
<i>Dual Container Locks:</i>	- Two front and two back.
<i>Approximate Hoist Weight:</i>	- 2874 lbs.
<i>Approximate Operating Times:</i>	- Down 15 sec. - On 46 sec. - Off 37 sec.
<i>Popular Options:</i>	- Semi Auto tarping system.
<i>Note:</i>	Some frame/truck modifications may be required.

***Note: Materials and product improvement is a continuous commitment at NEDLAND INDUSTRIES, INC. These specifications are subject to change without notice.***

*Mailing address:*  
P.O.Box 217  
Ridgeland, Wisconsin 54763

*Delivery address:*  
315 Railroad Street  
Ridgeland, Wisconsin 54763