



Specifications

Overall Length	120"
Overall Width	73"
Overall Height	57"
Compactor Capacity	3 Cu.Yds.
Platen Area	60" x 44" x 36"
Charge Opening	60" x 60"
Ram Penetration	12"
Twin Bypass Cylinders	4" x 60" x 2.5"
Line Pressure	2000 PSI
Max Line Pressure	2500 PSI
Max Ram Force	65000 LBS
Cycle Time	50 Seconds
Fluid Capacity	35 Gallons
Pump	15 GPM
Motor	20 HP/Tri-Volt, 3 Phase
Loading Height	51"
Approximate Weight	5250 LBS

Compactor Features

- .5" Steel AR plate floor with 3" & 6" structural channel, .25" Steel plate sides with 4" x 2" x .25" & 6" x 2" x .25" structural steel tubing
- Breaker bar 6" x 6" x 1" with hinged retaining teeth
- .5" hydraulic cylinder mounts
- Replaceable .5" UHMW polyethylene wear bars on ram sides, top and bottoms of platen for a smooth, quiet and near frictionless operation
- Weatherproof control panel and power pack
- Removable rear access panel
- Container guide rails

Options

- 15 HP 230, single phase
- Fluid Reservoir Heater
- Driver Pack Out
- Open Hopper (for loading dock or ground loading)
- Enclosed Doghouse with Door and Interlock
- Walk On or Drive On Deck with 42" Safety Rails
- Side Loading Hoppers
- Through-The-Wall Chutes
- Cart Dumper

Electrical/Hydraulic Features

- (PLC) Controlled power unit
- E-Stop Button
- Automatic Single Cycle
- Auto/Manual Selector
- Key Lock On/Off Switch
- Low Oil Sensor Shutdown
- Multi Cycle
- 80%-100% Full Lights
- Automatic Shutdown with Auto Safety Retract
- 15' remote
- Fluid level and temp Gauge
- Fluid Filled Pressure gauge
- Inlet Fluid Strainer
- 15' Hydraulic Hoses
- Left or Right Side Hydraulic Connections
- -40° **Biodegradable** hydraulic fluid