



Home of the EZroll off
SPECIFICATIONS DATA FOR
Model EZ24TR
EZroll off Trailer

<i>Hoist Rated capacity:</i>	24,000 lbs.
<i>Hoist Frame:</i>	6" x 3" x 3/8" wall tube.
<i>Main Frame:</i>	5" x 3" x 3/8" wall tube.
<i>Front Stops:</i>	5/8" Plate.
<i>Safety Lock:</i>	Automatic mechanical.
<i>Hoist Cylinder:</i>	2 - 4" x 48" x 2" Chrome Rods.
<i>Winch Cylinder:</i>	2 - 4" x 53" x 2" Nitro Rods.
<i>Cable:</i>	5/8" Cable.
<i>Outside Rollers:</i>	3" O.D. w/bronze bearing.
<i>Cable Sheaves:</i>	8" O.D. w/bronze bearing.
<i>Cable Travel:</i>	192"
<i>Hinge Shaft:</i>	1-1/2" with grease zerk.
<i>Dump Angle:</i>	51 degrees.
<i>Trailer Weight, Width, Length:</i>	6190 lbs., 101"W, 261"L.
<i>Approximate Operating Times:</i>	<ul style="list-style-type: none">- Down 20 sec.- On 50 sec.- Off 45 sec.
<i>Hydraulics:</i>	<ul style="list-style-type: none">- All hydraulics have safety lock valves.- Electric over hydraulic with manual override.- All wiring inside main rail tubes in protective Lomax conduit.- Wireless remote controlled operation.
<i>Dumpster Style:</i>	Tub.
<i>Maximum Dumpster Size:</i>	25 cubic yard x 14'
<i>Hitch:</i>	Pintel or Gooseneck.
<i>Jack:</i>	<ul style="list-style-type: none">- Hydraulic wireless remote controlled.
<i>Warranty:</i>	<ul style="list-style-type: none">- Five-year structural and axles.
<i>Other:</i>	<ul style="list-style-type: none">- GX390 Honda engine -Electric start, backup recoil start, 11/2 g.p.m. pump at 2000 psi.- UHMW slide pulley block.- All metal surfaces sandblasted and Powder Coated.- Dual container locks front and back.- Ratchet tie down rear container locks.- Hydraulic front tongue jack.- Aluminum diamond plate motor cover.- Dexter torflex, oil bath hubs on axles.- 235/75R 17.5 18-Ply steel belt radial. (Tires)- 2-Torflex axles 12,000 lbs. w/electric brakes.- Tread Plate side steps.
<i>Popular Options:</i>	<ul style="list-style-type: none">- Semi Auto Tarper or Fully Auto Tarper- Detachable Gooseneck

Note: Materials and product improvement is a continuous commitment at NEDLAND INDUSTRIES, INC. These specifications are subject to change without notice. 3/20/20